

Intro to Rails

MIS 21

A. Navarro, R. Alampay



INFORMATION SYSTEMS &
COMPUTER SCIENCE

Learning Objectives

- Determine the steps to start up a new Rails application
- Become familiar with Rails app conventions
- Learn how routes work
- Learn how to use generators



Ruby on Rails (RoR)

- An open source web application framework written in Ruby
- Utilizes well known design patterns such as ActiveRecord
- Created initially by David Heinemeier Hansson in 2004 as a result of his work on Basecamp(<http://basecamphq.com>)
- In 2008, merged with another well known ruby application framework called Merb
- The current iteration is v4.1 and is actively maintained by a staff of Ruby programmers



Sites built on Rails

- <http://basecamphq.com>
- Early version of <http://twitter.com>
- <http://github.com>
- <http://groupon.com>
- <http://hulu.com>
- <http://scribd.com>
- <http://assembla.com>



Ruby on Rails Core Principles

- Convention over configuration
- DRY – do not repeat yourself
- MVC – Model View Controller
- Fat Models, Skinny Controllers
- Agile Development



Creating a new rails application

- Creating an application is done by running the command

```
@Whis → ~ rbenv:(2.0.0-p0) rails new myapplication
```

- This creates a folder called “myapplication” which contains a rails project. This can be replaced with any app name.



Javascript Runtime

- Rails requires a javascript runtime in order to manipulate javascript and css files
- Find the line with “`rubyracer`” in your Gemfile and uncomment it then run `bundle install`
- Alternatively, you can install nodejs



rails folders

- app – contains your main application components
 - controllers – controllers handle web requests
 - models – models wrap the data found in our data stores
 - views – views contain our display templates
 - assets – contains files that are loaded by a browser (CSS, JS, Images)
- config – contains configuration code for our app
- db – contains code related to building the database
- lib – user created libraries/code (not a M,V or C)
- log – contains error logs
- public – contains any static files that don't change
- test – contains unit, functional and integration tests



Generators

- Most application code is created using generators
- Some gems include generators to ease in bootstrapping of code
- Generators follow standard rails conventions

```
@Whis → bookyappserver rbenv:(2.0.0-p0) git:(master) rails g --help  
Usage: rails generate GENERATOR [args] [options]
```



Models

- Models are classes used to represent rows in a database

Generator Syntax:

```
rails generate MODEL_NAME  
fieldname1:fieldtype1 fieldname2:fieldtype2
```

Example:

```
rails generate Entry name:string address:string  
number:string
```

- Fields are optional
- Field types are optional. If no field type is specified, the default is string
- Model generators also create a migration



Migrations

- Migrations are classes that define database structure.
- Saves user from writing SQL create statements for their database
- Found under the db/migrate folder
- To execute migrations run the command:

```
rake db:migrate
```

- To cancel the last executed migration run the command:

```
rake db:rollback
```



Controllers

- Controllers contain logic to handle web requests
- May use models to retrieve or save data
- Have actions (methods) that render corresponding views
 - A controller will have a corresponding folder under app/views

Generator Syntax:

```
rails generate CONTROLLER_NAME action1  
action2
```

Example:

```
rails generate Items index new edit
```

